

PALLET TRUCK SCALES

Making pallet truck scales that can endure the tough environments which various industrial applications throw at them, is no easy task, but EuroScales has for over 15 years been recognised by most of the largest companies in Europe as a leader in the field offering scales from simple weighing right through to complex systems with radio transmission linked to the clients database for warehousing, stock checking and stock control purposes.

Part of the package is a full service backup that includes, 12 months on-site parts and labour warranty after which EuroScales will then be at your disposal to offer annual contracts that include parts and labour as well as calibration certificates to meet the needs of clients with ISO 9000 certification.

Whatever your application EuroScales will endeavour to offer you a solution to your needs. Providing you with an accuracy of 0.1% of the applied load, you can be confident in the knowledge that the given reading is accurate.



Avenger

Avenger pallet truck scale with the added option of being a Trade Approved Scale, allowing you to charge for the weight shown on the display. Eliminating the need to take the goods to a static scale if you are charging by weight.



Laser/Concept

This is an upgradable scale where at some future date you can add a printer converting it into a Concept. The indicator has a clear LCD with indicators to show what state the scale is in e.g. motion, kg, lb, gross, net and centre of zero. Featuring a full numeric keyboard, also with zero, tare, recall keys and accumulation function.



Wizard – ATEX Approved

This particular model is made for hazardous areas where the environment is zone 1 or 2. With 10 tare entries it is ideal for use in barrel filling and decanting applications. The battery will last up to 30-50 hours between charges in auto power savings mode. Ex Rating – EEX Ib IIC T4.



PALLET TRUCK SCALES – SPECIFICATIONS



Standard Specifications

- 0.1% of the applied load
- 2300kg/2500kg capacity
- 0.5kg standard graduations
- Fast three stage battery charger
- Rechargeable 12v battery
- 12 month on-site warranty parts and labour
- Simple and easy to follow instructions

Options

- Capacity 3000kg
- Graduations 1kg, 0.5kg, 0.2kg
- Sleep mode between 1-20 minutes of inactivity
- Non standard widths
- Non standard lengths
- Forward facing display
- Rotating display
- Stainless steel versions
- Printers – thermal



Optional Extras

- Set point output
- Set point buzzer
- Deadmans brake
- Tandem wheels
- Calibration Certificate
- RF transmission
- Wet spec. wheels
- Stainless steel axles
- Wet spec. display
- Spare battery
- RS232 output
- Foot brake
- Hand brake
- LED display
- Quick lift pump
- Custom software
- ATEX EEX ib TTC T4
- Silicone cover



Dimensions

A	Fork Lengths:	:	910mm
		:	950mm
		:	1000mm
		:	1150mm
		:	1220mm
B	Fork Width	:	175mm
C	Width over forks	:	470mm
		:	540mm
		:	700mm
D	Max. height when lifted	:	210mm
E	Min. height when lowered	:	85mm

